

Unisolierte Quetschkabelschuhe

1


Gabelkabelschuhe

Nenngröße bis 6 mm² nach DIN 46234

16 mm² und 25 mm² Ringform offen

Werkstoff: E-Cu, Oberfläche: galvanisch verzinkt

* Normalausführung



1



Nennquerschnitt mm ²	Nenngröße	Art.-Nr.	Abmessungen in mm				Einheit Stück
			l	d	d ₁	a	
0,2 – 0,5	0,5 – 2,0	701544	9	2,2	5	5	100
	0,5 – 3,0	701546	9	3,2	5	5	100
	0,5 – 3,5	701548	12	3,7	7	5	100
	0,5 – 4,0	701550	12	4,3	7	5	100
	0,5 – 5,0	701552	12	5,3	8	5	100
0,5 – 1,5	1,0 – 3,0	701558	11	3,2	5,8	5	100
	1,0 – 3,5	701560	11	3,7	5,8	5	100
	1,0 – 4,0	701564	11	4,3	6,4	5	100
	1,0 – 4,0	701562*	12	4,3	7,0	5	100
	1,0 – 4,0	701566	12	4,3	8,1	5	100
	1,0 – 5,0	701568	13	5,3	9,6	5	100
	1,0 – 6,0	701570	13	6,4	11,0	5	100
	1,0 – 8,0	701572	14	8,4	14,0	5	100
	1,0 – 10,0	701574	17	10,5	15,0	5	100
	1,5 – 2,5	701580	11	3,2	5,8	5	100
1,5 – 2,5	2,5 – 3,0	701582	11	3,7	5,8	5	100
	2,5 – 3,5	701586	11	4,3	6,4	5	100
	2,5 – 4,0	701584*	12	4,3	7,0	5	100
	2,5 – 4,0	701588	12	4,3	8,1	5	100
	2,5 – 5,0	701590	13	5,3	9,6	5	100
	2,5 – 6,0	701592	13	6,4	12,0	5	100
	2,5 – 8,0	701594	16	8,4	14,0	5	100
	2,5 – 10,0	701596	18	10,5	15,0	5	100
	2,5 – 6,0	701602	14	4,3	8,5	6	100
	6,0 – 5,0	701604	14	5,3	9,0	6	100
2,5 – 6,0	6,0 – 6,0	701606	18	6,4	12,5	6	100
	6,0 – 8,0	701608	21	8,4	15,0	6	100
	6,0 – 10,0	701610	23	10,5	19,2	6	100
	10,0 – 5,0	701554	17	5,3	10,5	8	100
	10,0 – 6,0	701556	17	6,4	10,5	8	100
16,0	16,0 – 5,0	701576	20	5,3	11,0	10	100
	16,0 – 6,0	701578	20	6,4	11,0	10	100
25,0	25,0 – 5,0	701598	25	5,3	12,0	11	100
	25,0 – 6,0	701600	25	6,4	12,0	11	100


2

Stiftkabelschuhe

DIN 46230 und VG 88708 bis 16 mm²

und ähnliche Ausführungen

Werkstoff: E-Cu, Oberfläche: galvanisch verzinkt



2



Nennquerschnitt mm ²	Nenngröße	Art.-Nr.	Abmessungen in mm				Einheit Stück
			l	d	d ₁	a	
0,2 – 0,5	0,5	701752	14,5	1,0	1,2	5	100
0,5 – 1,5	1,0	701754	17,0	1,9	1,6	5	100
1,5 – 2,5	2,5	701756	17,0	1,9	2,3	5	100
2,5 – 6,0	6,0	701758	20,0	2,7	3,6	6	100
10,0	10,0	701760	25,0	4,3	4,5	10	100
16,0	16,0	701762	30,0	5,5	5,8	12	100
25,0	25,0	701764	33,0	7,0	7,0	14	100
35,0	35,0	701766	40,0	8,0	8,2	16	100
50,0	50,0	701768	45,0	9,5	9,5	19	100
70,0	70,0	701770	55,0	11,0	11,2	24	75
95,0	95,0	701772	55,0	12,5	13,5	24	60